

Solar Powered LED Flood Light System/ 14 Watts

SLR-FDL002-TPW-25W-001

FEATURES

- ◆ **Typical Runtime:** Up to 11 Hours daily at normal climate conditions
- ◆ **Long Operational Lifespan:** photometric design makes LEDs last up to 50,000 hours
- ◆ **Glare-Free Design:** Enhances night vision
- ◆ **Brightness:** 651 Lm
- ◆ **Safety Assurance:** LED lamp is C/UL Listed
- ◆ **Weatherproof:** Water resistant for outdoor applications
- ◆ **Variable Brightness:** Low/High/Off Switch for 2-Level Brightness

APPLICATIONS

- ◆ **Building Entrances**
- ◆ **Perimeters Security Lighting**
- ◆ **Parking Areas**
- ◆ **Parks & Walkway Illumination**
- ◆ **Pole-Mounted Area Lighting**
- ◆ **Up/Down Spot Lighting**



SLR-FDL002-TPW-25W-001

Emitted Color	True White LED
Input Power	14 Watts
Solar Panel	36 Watt, Mono Crystalline
Total Lumens	651 lm
M ax. Candela	261 CD
Efficacy	75 lm/W
CRI	>75
Color Temperature	4800K-5200k/ True White
Battery	Batt-12V-28Ah
Battery Technology	Deep-Cycle, Maintenance-Free, Sealed-Lead Acid
Input Voltage	12-14 VCD
Operating Temp.	-30 °C - +50 °C



Factory: Shaan Technologies private Limited,
Plot No 22, Sector C3, Export Processing Zone
Karachi, Pakistan

Phone: +92-21-35080954 Fax: +92-21-35080957

City Sales office : Shaantech Energy Solutions (Pvt) Limited
47/H-1, Block 6, P.E.C.H.S., Karachi.

E-mail: info@shaantech.com, Sales-admin@shaantech.net
Website: www.shaantech.com

© 2013 Shaan Technologies Private Limited.

To order ShaanTech Solar products, Please Call our Sales office
or contact the Distributor /Sales Representative in your area.

Visit our website to find your local Distributor or Representative
from our Nationwide network:

www.shaantech.com